

imagine monitors as sharp and detailed as your vision.



Samsung T-Series
SyncMaster 943T/245T/275T+/305T High-Definition LCD Monitors for Professional Applications



Samsung 943T/245T/275T+/305T

High-Definition LCD Monitors for Professional Applications



imagine being able to see everything that you're thinking. Every detail of your ideas will come to life when you create them on the Samsung 943T, 245T, 275T+ and 305T high-definition monitors. They're the perfect monitors for professionals who, like us, turn ideas to reality on a daily basis. With the Samsung 943T, 245T, 275T+ and 305T, it's not hard to imagine.

S-PVA panels appeal to a wider audience.

Whether you're showing ideas to a group of two or a group of 10, everyone will be able to see. Samsung's S-PVA (Super Pattern Vertical Alignment) panel technology produces wide viewing angles of up to 178°/178° (CR>=10), which is up to 10° greater (horizontal and vertical) than normal TN panels. Even the people on the sides will be able to see bright, accurate color from any angle of view.






S-PVA Panel

TN Panel

Enhanced CCFL technology for up to 102% NTSC color gamut.

When your ideas begin to take shape, we'll make sure they look their best. Typical CCFL (Cold Cathode Fluorescent Lamp) LCD backlight technology is able to reproduce just 82% of the NTSC color gamut. Samsung's Enhanced CCFL technology reproduces up to 102% of the NTSC color gamut. You'll be able to reproduce colors you never could on LCD monitors before.



HDMI for the highest definition.



The details are what separate an average idea from a great idea. And they're what separate an average monitor from a great one.



The 245T and 275T+ give you all the detail you need with an HDMI (High-Definition Multimedia Interface) connection and HDCP (High-bandwidth Digital Content Protection).

HDMI and HDCP work together to support uncompressed digital streams of standard, enhanced or high-definition video. You'll have the highest re4solution images possible, and a picture that's second to none.



Fast 6 ms G to G response for sharp motion graphics.

Not everything you do on your Samsung will be a still picture. You might be viewing a film clip. You might be editing a sales video. You might be watching the playoffs with the gang after work one night. Whatever the case may be, the 943T, 245T, 275T+ and 305T feature fast 6 ms Gray-to-Gray response times, for sharp, smear-free, impressive motion video.















Wide applications in the business world.

Desktop publishers will find the wide screens of the 245T, 275T+ and 305T are perfect for layouts, including spreads. The extra room more easily accommodates application tool palettes.

Musicians and producers will benefit from the wide screens by being able to see more of a waveform at once. Recording, editing and producing is easier than ever.

CAD/CAM engineers and designers will find their work is made easier by the high resolution and 16:10 ratio.

Those in the medical profession will have a valuable diagnostic tool due to the large screen, high resolution and gamma control, for ultimate image clarity and detail.

And whether you develop games for a living or you just like to play, nothing compares to gaming on a huge, wide, colorful, sharp display.

Which industry would benefit most from a Samsung high-definition monitor? No matter which one you choose, the industry that would definitely benefit the most from a Samsung high-definition monitor is yours.



MagicColor for color exactly the way you want it.



Brilliant natural color is as important to us as it is to you. So we invented our exclusive MagicColor technology. MagicColor offers five modes, to let you adjust the color exactly the way you like it. Full mode enhances the overall color. Intelligent mode enhances the color without affecting delicate skin tones. And Demo mode uses a split screen to let you compare color corrections to your original picture.

The perfect picture with exclusive MagicBright 3 technology.



MagicBright 3 is an exclusive Samsung technology that gives you the optimum viewing experience, no matter what's on your screen. Seven presets let you instantly select from modes that include Custom, Text, Internet, Game, Sport, Movie and Dynamic Contrast. (Excludes 305T.)

| Specifications | | 943T | 245T | 275T+ | 305T |
|-------------------------------------|--|---|---|---|--|
| Display | Туре | PVA | SPVA | SPVA | SPVA |
| | Viewable Size | 19" | 24" Wide | 27" Wide | 30" Wide |
| | Native Resolution | 1280 x 1024 | 1920 x 1200 | 1920 x 1200 | 2560 x 1600 |
| | Pixel Pitch | 0.294 | 0.270 | 0.303 | 0.250 |
| | Aspect Ratio | 5:4 | 16:10 | 16:10 | 16:10 |
| | Contrast Ratio (Typical/Dynamic) | 1500:1/10000:1 | 1000:1/1500:1 | 1000:1/3000:1 | 1000:1 (typical) |
| | Viewing Angle (Horizontal/Vertical) | 178°/178° (CR>10) | 178°/178° (CR>10) | 178°/178° (CR>10) | 178°/178° (CR>10) |
| | | , , | , , | , , | · , |
| | Response Time | 25ms | 6ms (GTG) | 6ms (GTG) | 6ms (GTG) |
| | Light Source | CCFL | CCFL | CCFL | CCFL |
| | Wide Color Gamut (NTSC) | 82% | 97% | 97% | 102% |
| | Brightness (Typical) | 250 cd/m ² | 300 cd/m ² | 500 cd/m ² | 300 cd/m ² |
| | Panel Surface | Matte | Matte | Matte | Matte |
| | Maximum Color Supported | 16.7M | 16.7M | 16.7M | 16.7M |
| Video Input Signal | Analog | Analog RGB | Analog RGB, Component, CVBS, | Analog RGB, Component, CVBS, | N/A |
| | Androg | Analog Nab | S-video | S-video | IVA |
| | Digital | DVI | DVI, HDMI | DVI, HDMI | Dual Link DVI |
| | • | | | | |
| | Frequency | 30~81kHz(H) / 56~75Hz(V) | 30~81kHz(H) / 56~75Hz(V) | 30~81kHz(H) / 56~75Hz(V) | 49.3~98.7kHz(H) / 60Hz(V) |
| | Sync | H/V Separated, Composite H/V, Sync | H/V Separated, Composite H/V, Sync | H/V Separated, Composite H/V, Sync | H/V Separated |
| | | on Green | on Green | on Green | |
| Compatibilty | PC | Windows Vista Premium Certification, XP, 2000, 98 | Windows Vista Premium Certification, XP, 2000, 98 | Windows Vista Premium Certification, XP, 2000, 98 | Windows Vista Premium Certification, XP, 2000, 98 |
| | Mac | Mac OS Leopard, X, 9 | Mac OS Leopard, X, 9 | Mac OS Leopard, X, 9 | Mac OS Leopard, X, 9 |
| Input Connectors | | 15-pin D-sub, DVI-D | 15-pin D-sub, Component, CVBS, | 15-pin D-sub, Component, CVBS, | DVI-D (Dual link) |
| | | TO PILL GOD, EVI D | S-video, DVI-D, HDMI, 3-pin AC plug (CEE22) | S-video, DVI-D, HDMI, 3-pin AC plug (CEE22) | 5 (Statilling |
| Power | Voltage | AC 100-240 ~ VAC (± 10%), 60 / 50 Hz ± 3 Hz | AC 100-240 ~ VAC (± 10%), 60 / 50 Hz ± 3 Hz | AC 100-240 ~ VAC (± 10%), 60 / 50 Hz ± 3 Hz | AC 100-240 \sim VAC (\pm 10%), 60 / 50 Hz \pm 3 Hz |
| | Consumption (Max/Standby) | 34 watts (max)/<1 watts (DPMS mode) | 130 watts (max)/<2 watts (DPMS mode) | | |
| Controls | Basic | Power, Auto Adjustment, Source, | Power, Auto Adjustment, Source, | Power, Auto Adjustment, Source, | Power, Brightness up/down |
| Features | Dasic | Brightness up/down, MagicBright 3 presets, OSD Menu | Brightness up/down, MagicBright 3 presets, OSD Menu | Brightness up/down, MagicBright 3 presets, OSD Menu | Tower, Drightness up/down |
| | Advanced | Picture (Brightness, Contrast, Magic Bright), Color (MagicColor, Color Tone, Color Control, Color Effect, Gamma), Image (Coarse, Fine, Sharpness, HV Position, OSD (Language, HV Position, Transparency, Display Time), Setup (Auto Source, Reset, Off Timer, | Picture (Brightness, Contrast, Magic Bright), Color (MagicColor, Color Tone, Color Control, Color Effect, Gamma), Image (Coarse, Fine, Sharpness, IHV Position, OSD (Language, H/V Position, Transparency, Display Time), Setup (Auto Source, Reset, Off Timer, | Picture (Brightness, Contrast, Magic Bright), Color (MagicColor, Color Tone, Color Control, Color Effect, Gamma), Image (Coarse, Fine, Sharpness, In/V Position, OSD (Language, H/V Position, Transparency, Display Time), Setup(Auto Source, Reset, Off Timer, | N/A |
| | Dlug & Dloy | Customized Key, Image Size) DDC 2B/DDC-CI | Customized Key, Image Size) DDC 2B/DDC-CI | Customized Key, Image Size) DDC 2B/DDC-CI | DDC 2B/DDC-CI |
| Features | Plug & Play Stand | 4-way adjustable (height, swivel, tilt, | 4-way adjustable: Height Adjustable | Height Adjustable (80mm), Swivel, Tilt | Height Adjustable (80mm), Swivel, Tilt |
| | | rotate) | (100mm), Swivel, Tilt, Rotate | | |
| | Wall Mount (VESA) | 75mm | 200 x 100 mm | 200mm x 100mm | 200mm x 100mm |
| | Cabinet Color | Matte | Matte | Matte | Matte |
| Special Features | | Built-in USB 2.0 (1up/2down) | PIP/PBP, full HD support (1080p), MPA (Motion Picture Accelator), Built-in USB 2.0 (1up/4down), Clear PBP | PIP/PBP, Built-in USB 2.0 (1up/4down), Clear PBP | Built-in USB 2.0 (1up/4down) |
| Magic Technologies | MagicColor (Full and Intellignet Mode) | | | | N/A |
| | - · · · · · · · · · · · · · · · · · · · | | - | <u>-</u> | = |
| | MagicBright 3 (Text, Internet, Mode, Game, Sports, Custom and Print View mode) | - | - | - | _ |
| | MagicTune (With Asset Management) | | | | N/A |
| | MagicStand HAS (Height Adjustable, Swivel, Tilt, Pivot) | | | N/A | N/A |
| | MagicRotation (Image Rotation With Software) | | | N/A | N/A |
| | MagicAutoRotation (Automatic Image Rotation) | N/A | | N/A | N/A |
| | MagicSpectrum (Wide Color Gamut) | N/A | | | • |
| Ongrating Conditions | | | _ | | _ |
| Operating Conditions | Temperature/Humidity | 10°C ~ 40°C/10% ~ 80% | 10°C ~ 40°C/10% ~ 80% | 10°C ~ 40°C/10% ~ 80% | 10°C ~ 40°C/10% ~ 80% |
| Dimensions and | Product Dimension (w/Stand, W x H x D) | 16" x 15" x 7.5" | 22.1" x 18.1" x 9.8" | 24.8" x 19.1" x 11 | 27.2" x 19.8" x 11 |
| | Product Dimension (w/o Stand, W x H x D) | 16" x 14" x 2.5" | 22.1 x 14.5" x 3.6" | 24.8" x 16.1" x 3.1" | 27.2" x 17.7" x 3.3" |
| | 1 | 18.9" x 8" x 16.2" | 25.7" x 20.4" x 11.9" | 28.9" x 22.3" x 13.8" | 31.3" x 22.7" x 13.7" |
| | Shipping Carton Dimension (W x H x D) | | 19.4 lbs. | 22.9 lbs. | 26.5 lbs. |
| Weight | Shipping Carton Dimension (W x H x D) Product Weight (With Stand) | 10.7 lbs. | 19.4 105. | EE.O IDO. | |
| Weight | Product Weight (With Stand) | 10.7 lbs. 14.3 lbs. | 26.2 lbs. | 31.3 lbs. | 33 lbs. |
| Weight Product Weight | Product Weight (With Stand) Shipping Weight | 14.3 lbs. | 26.2 lbs. | 31.3 lbs. | 33 lbs. |
| Weight Product Weight | Product Weight (With Stand) Shipping Weight Emission Standard | 14.3 lbs. TCO '03 | 26.2 lbs. TC0 '03 | 31.3 lbs. TCO '03 | 33 lbs. TCO '99 |
| Weight Product Weight | Product Weight (With Stand) Shipping Weight Emission Standard RoHS Compliant/Energy Star Compliant | 14.3 lbs. TCO '03 | 26.2 lbs. TC0 '03 | 31.3 lbs. TCO '03 | 33 lbs. TCO '99 ■ |
| Weight Product Weight Environmental | Product Weight (With Stand) Shipping Weight Emission Standard | 14.3 lbs. TCO '03 | 26.2 lbs. TC0 '03 | 31.3 lbs. TCO '03 | 33 lbs. TCO '99 |
| Weight Product Weight | Product Weight (With Stand) Shipping Weight Emission Standard RoHS Compliant/Energy Star Compliant | 14.3 lbs. TCO '03 CCFL panel contains mercury, please | 26.2 lbs. TC0 '03 CCFL panel contains mercury, please | 31.3 lbs. TCO '03 ■ CCFL panel contains mercury, please | 33 lbs. TCO '99 ■ CCFL panel contains mercury, please |
| Weight Product Weight | Product Weight (With Stand) Shipping Weight Emission Standard RoHS Compliant/Energy Star Compliant Product Recyclability | 14.3 lbs. TCO '03 CCFL panel contains mercury, please dispose of properly | 26.2 lbs. TCO '03 CCFL panel contains mercury, please dispose of properly | 31.3 lbs. TCO '03 CCFL panel contains mercury, please dispose of properly | 33 lbs. TCO '99 ■ CCFL panel contains mercury, please dispose of properly |

